



MATERIAL SAFETY DATA

Chemtrec 24-Hour Emergency Telephone

Domestic North America (800) 424-9300

International (800) 527-3887

This MSDS complies with 29 CFR 1910.1200 (Hazard Communications)

1. Product and Supplier Identification

Product Name: Fiberlay
Product Number: 262PCF, 262PCG, 262PCQ, 262PCD
Date of Prep: 10-25-10
Product Type: Mark 2 Curative
Supplier: Fiberlay Inc.
 24 S. Idaho S.
 Seattle, Wa 98134
 (206)782-0660

2. Composition/Information On Ingredients

CAS No.	Chemical Name	% (by weight)	OSHA PEL	ACGIH TLV	Other Limits
	Polyether Polyols Amine Based	50	NE	NE	NE
6846500	Polymeric Plasticizer	50	NE	NE	NE

3. Hazards Identification

Hazard Category: Acute

- Avoid oxidizers
- May cause eye and skin irritation
- Routes of entry:
 - ✓ Skin contact
 - ✓ Eye contact

Physical form: Liquid

Color: Clear

Odor: Slight fruity odor

Health Hazards:

Acute: (Short Term)

On the basis of available information, exposure to this product is not expected to produce any significant adverse human health effects when recommended safety precautions are followed.

Chronic: (Delayed)

On the basis of available information, exposure to this product is not expected to produce any significant adverse human health effects when recommended safety precautions are followed.

Signs & Symptoms:

Skin and eye irritation

Medical Conditions Generally aggravated by Exposure:

Skin and eye irritation

4. First Aid Measures

Eyes:

- Flush eyes with water for at least 15 minutes
- Contact a physician

Skin:

- Remove contaminated clothing
- Wash affected area with isopropyl alcohol followed by soap and water

Ingestion:

- DO NOT induce vomiting
- Drink 1-2 glasses of water and contact a physician
- Do not give anything by mouth to an unconscious person

Inhalation:

- Remove person to fresh air
- If person is not breathing, give mouth-to-mouth resuscitation
- Contact a physician

Other Health Warnings:

- Wash hands thoroughly after handling this material before eating, smoking, etc.

5. Fire Fighting Measures

Flash Point: > 275°F

Flammable Limits - LEL: NE

Flammable Limits - UEL: NE

Fire and Explosion Hazards:

None known

Extinguishing Media:

- Foam
- Water Fog
- Carbon Dioxide or Dry extinguishers

Fire Fighting Instructions:

Firefighters should wear a self-contained breathing apparatus and protective clothing

6. Accidental Release Measures

- Cover liquid with an absorbent material (sawdust, vermiculite or wet sand)
- After material is absorbed, scoop up and place in containers for disposal

7. Handling and Storage

Handling:

Avoid skin and eye contact

Storage:

- Store in cool dry place in tightly sealed containers
- Protect from heat and moisture contamination

8. Exposure Controls / Personal Protection

Engineering Controls:

- Local Exhaust: Use in Ventilated area
- Mechanical (General): Recommended

Eye Protection:

- Safety glasses or goggles

Skin Protection:

- Impervious rubber gloves

Respiratory Protection:

- None needed at normal temperatures
- Use a self contained breathing apparatus under emergency conditions

Other:

- An apron or suitable clothing to prevent skin contact

9. Physical and Chemical Properties

Boiling Point:	> 300°F	Spec. Physical Form	Liquid
Specific Gravity	0.99	Odor:	Fruity odor
Evaporation Rate:	NE	Color:	Clear
Melting Point:	NA	% Volatiles by volume	Negligible
Vapor Pressure:	NE	Solubility in Water:	Slight
Vapor Density:	NE	Volatility @ 75°F	Very Low

10. Stability and Reactivity

Stability:

- Stable

Materials and Conditions to Avoid:

- Strong oxidizers

Hazardous Polymerization:

- Will not occur

Hazardous Decomposition or By-Products:

- High temperatures and burning conditions may release incompletely burned carbon products:
 - ✓ Carbon monoxide
 - ✓ Carbon dioxide

11. Toxicological Information

None available

12. Ecological Information

None available

13. Disposal Considerations

Waste Disposal Method:

- Waste must be disposed of in accordance with federal, state and local environmental regulations
- Incinerate or bury in a licensed facility
- Containers may be disposed of or reclaimed in a routine manner

14. Transport Information

Shipping Name: Plastic Liquid Resin Material

Item: 156240

DOT Shipping Class: Class 60

Non-Hazardous

15. Regulatory Information

SARA 313 Information:

This product doesn't contain the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372

16. Other Information

NFPA Hazard Classification

Health: 1 Flammability: 1 Reactivity: 0 Special Hazards: 1

HMIS Hazard Classification

Health: 1 Flammability: 1 Reactivity: 0 Protection: C

Preparation Date: 10-25-10

Prepared by: Fiberlay Inc

Comments: This Material Safety Data Sheet was prepared using information provided by Hyperlast North America, Fiberlay Inc, and CCINFO

Manufacturer Disclaimer: this information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of Fiberlay, Inc. The data on this sheet relates only to the specific materials designated herein. Fiberlay Inc., assumes no legal responsibility for use or reliance upon this data.

Revisions: None