



Safety Data Sheet

SDS No. 644A

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Part A for Brush-On[®] 40, 50, 60; EZ-Mix[®] 40; PMC[®] 121-30, PMC[®]-744, PMC[®]-746, PMC[®]-770, PMC[®]-790, PMC[®]-844; Renew[™] UR-40, UR-90; Reoflex[®] 20, 30, 40; UreCoat[®]; Vytaflex[®] 10, 20, 30, 40

General Use: Polyurethane Elastomer

Manufacturer: Smooth-On, Inc.,
5600 Lower Macungie Rd., Macungie, PA 18062
Phone (610) 252-5800, FAX (610) 252-6200

Emergency Contact: Chem-Tel
Domestic: 800-255-3924 International: 813-248-0585

Section 2 - Hazards Identification

Classification of the substance or mixture

Acute toxicity, oral-Category 4
Acute toxicity, inhalation-Category 4
Acute toxicity, dermal-Category 4
Skin irritation-Category 2
Eye irritation-Category 2A
Specific target organ toxicity-single exposure-Category 3 (respiratory)
Carcinogenicity-Category 2
Reproductive toxicity-Category 1B

GHS Label elements, including precautionary statements

Pictogram:



Signal word: Danger

| | | |
|-------------------------|--------------------|---|
| Health Hazards | H302 + H312 + H332 | Harmful if swallowed, in contact with skin or if inhaled |
| | H315 | Causes skin irritation |
| | H319 | Causes serious eye irritation |
| | H335 | May cause respiratory irritation |
| | H351 | Suspected of causing cancer. |
| | H360 | May damage fertility or the unborn child. |
| General Precautions: | P101 | If medical advice is needed, have product container or label at hand. |
| | P102 | Keep out of reach of children. |
| | P103 | Read label before use. |
| Prevention Precautions: | P261 | Avoid breathing dust/fume/gas/mist/vapors/spray. |
| | P264 | Wash skin thoroughly after handling. |
| | P270 | Do not eat, drink or smoke when using this product. |
| | P271 | Use only outdoors or in a well-ventilated area. |

| | | |
|--------------|--------------------|--|
| | P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| Response | P301 + P312 | IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. |
| Precautions: | P302 + P352 | IF ON SKIN: Wash with plenty of soap and water. |
| | P304 + P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| | P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| | P312 | Call a POISON CENTER or doctor/physician if you feel unwell. |
| | P322 | Rinse mouth. |
| | P330 | If skin irritation occurs: Get medical advice/attention. |
| | P332 + P313 | If eye irritation persists: Get medical advice/attention. |
| | P337 + P313 | Take off contaminated clothing. |
| | P362 | Store in a well-ventilated place. Keep container tightly closed. |
| Storage | P405 | Store locked up. |
| Precautions: | | |
| Disposal | P501 | Dispose of contents/container to local, state and federal laws |
| Precautions: | | |

Hazards not otherwise classified (HNOC) or not covered by GHS – lachrymator

Section 3 - Composition / Information on Ingredients

The following ingredients are hazardous according to 2012 OSHA Regulation 29 CFR 1910.1200 criteria:

| CAS | Component | Concentration |
|-----------|--|---------------|
| 9057-91-4 | Poly[oxy(methyl-1,2-ethanediyl)], α -hydro- Ω -hydroxy, polymer with 1,3 diisocyanatomethylbenzene | > 80% |
| 584-84-9 | Toluene-2,4-diisocyanate | < 1.0% |
| 91-08-7 | Toluene-2,6-disocyanate | <0.2% |

The following ingredient(s) are hazardous according to California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65).

| CAS | Component | Concentration |
|------------|----------------------|---------------|
| 28553-12-0 | Diisononyl phthalate | <25% |

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately.

Eye Contact: Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact: In case of skin contact, wash thoroughly with soap and water.

Ingestion: Do not induce vomiting unless instructed by a physician. Never give anything by mouth to an unconscious person.

After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

Flammable Classification: Non-Flammable

Extinguishing Media: Water Fog, Dry Chemical, and Carbon Dioxide Foam

Unusual Fire or Explosion Hazards: None known.

Fire-Fighting Instructions: Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors. Either allow fire to burn under controlled conditions or extinguish with foam or dry chemical. Try to cover liquid spills with foam.

Further information: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure demand or positive-pressure mode.

Section 6 - Accidental Release Measures

Spill /Leak procedures: Only properly protected personnel should remain in the spill area; dike and contain spill; absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution. Stop or reduce discharge if it can be done safely.

Environmental precautions: No special environmental precautions required.

Section 7 - Handling and Storage

Handling Precautions: Use good general housekeeping procedures. Wash hands after use.

Storage Requirements: Keep container(s) tightly closed and properly labeled. Store in cool, dry, well ventilated place away from heat, direct sunlight, strong oxidizers and any incompatibles. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous. Avoid water contamination.

Section 8 - Exposure Controls / Personal Protection

| | | | |
|--------------------------|----------|-----------|--|
| Toluene-2,6-diisocyanate | 91-08-7 | ACGIH TLV | TWA: 0.005 ppm STEL: 0.02 ppm |
| Toluene-2,4-diisocyanate | 584-84-9 | OSHA PEL | CLV: 0.02 ppm 0.14 mg/m ³ TWA: 0.005 ppm 0.04 mg/m ³ STEL: 0.02 ppm 0.15 mg/m ³ |
| | | ACGIH TLV | TWA: 0.005 ppm STEL: 0.02 ppm |

Respiratory Protection: Respiratory protection is not normally required when using this product with adequate ventilation. Should a respirator be needed, follow OSHA respirator regulations 29 CFR 1910.134 and European Standards EN 141, 143 and 371; wear an MSHA/NIOSH or European Standards EN 141, 143 and 371 approved respirators equipped with organic vapor cartridges.

Hand Protection: Wear chemically resistant gloves such as butyl rubber, neoprene or PVC.

Eye Protection: Safety glasses with side shields per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Other Protective Clothing/Equipment: Additional protective clothing or equipment is not normally required. Provide eye bath and safety shower.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics. Wash thoroughly after handling.

Section 9 - Physical and Chemical Properties

| | |
|---|---|
| Appearance : clear yellow viscous liquid | Vapor Pressure: None (Polymeric Resin) |
| Odor/Threshold: sharp pungent odor | Vapor Density (Air=1): >1 |
| pH: N.A. (non-aqueous) | Specific Gravity (H₂O=1, at 4 °C): 1.04 |
| Melting Point/Freezing Point: N.A. | Water Solubility: Insoluble |
| Low/High Boiling Point: N.A. | Partition coefficient: Not available |
| Flash Point: >270 °F | Auto-ignition temperature: Not available |
| Evaporation Rate: Not available | Decomposition temperature: Not available |
| Flammability: f.p. at or above 200 °F | Viscosity: <5000 centipoise |
| UEL/LEL: Not available | % Volatile: Nil |

Section 10 - Stability and Reactivity

Stability: These products are stable at room temperature in closed containers under normal storage and handling conditions.

Conditions to avoid: >120 °F.

Polymerization: Risk of polymerization.

Chemical Incompatibilities: Reacts with water with formation of carbon dioxide. Risk of bursting. Reacts with alcohols, acids, alkalis, amines. Risk of exothermic reaction.

Hazardous Decomposition Products: Thermal oxidative decomposition can produce carbon oxides, hydrogen cyanide, nitrogen oxides, aromatic isocyanates, gasses/vapors, and traces of incompletely burned carbon compounds.

Section 11- Toxicological Information

Skin Corrosion/Irritation: no data

Serious Eye Damage/Irritation: no data

Respiratory/Skin Sensitization: no data

Germ Cell Mutagenicity: no data

Carcinogenicity: toluene diisocyanate has been classified by IARC as a Group 2B (Possibly carcinogenic to humans. NTP has listed it as a carcinogen.

Reproductive Toxicity: no data

Specific Target Organ Toxicity – Single Exposure: no data

Specific Target Organ Toxicity – Repeated Exposure: no data

Aspiration Hazard: no data

Acute Toxicity: no data

Chronic Exposure: no data

Potential Health Effects – Miscellaneous: no data

Section 12 - Ecological Information

Toxicity: no data

Persistence and Degradability: no data

Bioaccumulative Potential: no data

Mobility in Soil: no data

Other Adverse Effects: no data

Section 13 - Disposal Considerations

Disposal: Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore to not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

Section 14 - Transport Information

DOT
Not Regulated

IATA
Not Regulated

IMDG
Not Regulated

Section 15 - Regulatory Information

United States EPA Regulations:

CERCLA Hazardous Substance (40 CFR 302.4) listed specific per RCRA, Sec. 3001; CWA, Sec. 311 (b)(4); CWA, Sec. 307(a), CAA, Sec. 112

| Chemical Name | CAS | RQ | Reportable Content |
|--------------------------|----------|--------|--------------------|
| Toluene-2,6-diisocyanate | 91-08-7 | 100 lb | <0.2% |
| Toluene-2,4-diisocyanate | 584-84-9 | 100 lb | <1.0% |

SARA EHS (Extremely Hazardous Substance) (40 CFR 355):

| Chemical Name | CAS | RQ | Reportable Content |
|--------------------------|----------|--------|--------------------|
| Toluene-2,6-diisocyanate | 91-08-7 | 100 lb | <0.2% |
| Toluene-2,4-diisocyanate | 584-84-9 | 100 lb | <1.0% |

These products contain the following chemicals that are subject to release reporting requirements under **section 313 of SARA Title III**.


| Chemical Name | CAS | RQ | Reportable Content |
|--------------------------|----------|--------|--------------------|
| Toluene-2,6-diisocyanate | 91-08-7 | 100 lb | <0.2% |
| Toluene-2,4-diisocyanate | 584-84-9 | 100 lb | <1.0% |

TSCA Inventory Status (40 CFR710): All components of this formulation are listed in the TSCA Inventory.

California Proposition 65: This product contains a chemical known to the state of California to cause cancer, birth defects or other reproductive harm.

16 - Other Information

| HMIS | |
|------|---|
| H | 2 |
| F | 1 |
| R | 1 |



NFPA

Revision: 2

Date Prepared: July 23, 2015

Glossary: ACGIH-American Conference of Governmental Industrial Hygienists; ANSI-American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS-Chemical Abstract Service; Chemtrec-Chemical Transportation Emergency Center (US); CHIP-Chemical Hazard Information and Packaging; DSL-Domestic Substances List; EC-Equivalent Concentration; EH40 (UK)-HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA-Emergency Planning and Community Right-To-Know Act; ESL-Effects screening levels; GHS-Globally Harmonized System of Classification and Labelling of Chemicals; HMIS-Hazardous Material Information Service; IATA-International Air Transport Association; IMDG-International Maritime Dangerous Goods Code; LC-Lethal Concentration; LD-Lethal Dose; LEL-Lower Explosion Level; NFPA-National Fire Protection Association; OEL-Occupational Exposure Limit; OSHA-Occupational Safety and Health Administration, US Dept. of Labor; PEL-Permissible Exposure Limit; SARA (Title III)-Superfund Amendments and Reauthorization Act; SARA 313-Superfund Amendments and Reauthorization Act, Section 313; SCBA-Self-Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TCEQ-Texas Commission on Environmental Quality; TLV-Threshold Limit Value; TSCA-Toxic Substances Control Act Public Law 94-469; TWA-Time Weighted Value; UEL-Upper Explosion Level; US DOT-US Department of Transportation; WHMIS-Workplace Hazardous Materials Information System.

Disclaimer: The information contained in this Safety Data Sheet (SDS) is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This SDS is prepared to comply with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) as prescribed by the United States (US) Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 (REACH).

Classifications of the chemical in accordance with 29 CFR 1910.1200, signal word, hazard and precautionary statement(s), symbol(s) and other information are based on listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS and EC No 1907/2006 and are considered trade secrets under US Federal Law (29 CFR and 40 CFR), Canadian Law (Health Canada Legislation), and European Union Directives.



Safety Data Sheet

SDS No. 419B

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Part B for: Brush-On[®] 50; Econ[®] 60 and 80; EZ-Spray[®] Plastic; Foam-iT! 4, 4 Black, 5, 8; Plasti-Paste[®] and Plasti-Paste[®] II; PMC[®] 121-30 Dry and Wet, PMC[®] 770, PMC[®] 844; Renew[™] UR-40, UR-60; ReoFlex[®] 20 Dry, 30 Dry and Wet, 40 Dry and Wet, 50 Dry and Wet, 60 Dry and Wet; Shell Shock[®] Fast and Slow; Smooth-Cast[®] 305, 310, 321, 322, 385; Task[®] 5, 6, 18; Urethane 4400; VytaFlex[®] 10, 20, 30, 40, 50, 60

Part A for: TerraCon[®] 55; Urethane 4040

General Use: Polyurethane Elastomer

Manufacturer: Smooth-On, Inc.,
5600 Lower Macungie Rd., Macungie, PA 18062
Phone (610) 252-5800, FAX (610) 252-6200

Emergency Contact: Chem-Tel
Domestic: 800-255-3924 International: 813-248-0585

Section 2 - Hazards Identification

Classification of the substance or mixture:

Not a hazardous substance or mixture according to United States Occupational Safety and Health Administration (OSHA) 2012 Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) and Council Directive 1999/45/EC and its subsequent amendments.

General

Precautions: P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.

Hazards not otherwise classified (HNOC) or not covered by GHS –

This product contains a chemical known to be hazardous according to California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65). (See also Section 15)

Section 3 - Composition / Information on Ingredients

No ingredients are hazardous according to 2012 OSHA Regulation 29 CFR 1910.1200 criteria.

The following ingredients are hazardous according to California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65).

| CAS | Component | Concentration |
|------------|----------------------|---------------|
| 28553-12-0 | Diisononyl phthalate | 5% - 50% |

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately.

Eye Contact: Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact: In case of skin contact, wash thoroughly with soap and water.

Ingestion: Do not induce vomiting unless instructed by a physician. Never give anything by mouth to an unconscious person.

After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

Flammable Classification: Non-Flammable

Extinguishing Media: Water Fog, Dry Chemical, and Carbon Dioxide Foam

Unusual Fire or Explosion Hazards: None known.

Fire-Fighting Instructions: Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors. Either allow fire to burn under controlled conditions or extinguish with foam or dry chemical. Try to cover liquid spills with foam.

Further information: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure demand or positive-pressure mode.

Section 6 - Accidental Release Measures

Spill /Leak procedures: Only properly protected personnel should remain in the spill area; dike and contain spill; absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution. Stop or reduce discharge if it can be done safely.

Environmental precautions: Prevent spillage from entering drains.

Section 7 - Handling and Storage

Handling Precautions: Use good general housekeeping procedures. Wash hands after use.

Storage Requirements: Keep container(s) tightly closed and properly labeled. Store in cool, dry, well ventilated place away from heat, direct sunlight, strong oxidizers and any incompatibles. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous. Avoid water contamination.

Section 8 - Exposure Controls / Personal Protection

Respiratory Protection: Should a respirator be needed, follow OSHA respirator regulations 29 CFR 1910.134 and European Standards EN 141, 143 and 371; wear an MSHA/NIOSH or European Standards EN 141, 143 and 371 approved respirators equipped with organic vapor cartridges.

Hand Protection: Wear any liquid-tight gloves such as butyl rubber, neoprene or PVC.

Eye Protection: Safety glasses with side shields per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Other Protective Clothing/Equipment: Additional protective clothing or equipment is not normally required. Provide eye bath and safety shower.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics. Wash thoroughly after handling.

Section 9 - Physical and Chemical Properties

Appearance : Clear colorless liquid
Odor/Threshold: Mild odor
pH: N.A. (non-aqueous)
Melting Point/Freezing Point: N.A.
Low/High Boiling Point: N.A.
Flash Point: >300 °F
Evaporation Rate: Not available
Flammability: f.p. at or above 200 °F
UEL/LEL: Not available

Vapor Pressure: None (Polymeric Resin)
Vapor Density (Air=1): >1
Specific Gravity (H₂O=1, at 4 °C): 1.05-1.25
Water Solubility: Insoluble
Partition coefficient: Not available
Auto-ignition temperature: Not available
Decomposition temperature: Not available
Viscosity: 100 - 500 centipoise
% Volatile: Nil

Section 10 - Stability and Reactivity

Stability: These products are stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization cannot occur.

Chemical Incompatibilities: Strong bases, and acids.

Hazardous Decomposition Products: Thermal oxidative decomposition can produce carbon oxides and traces of incompletely burned carbon compounds.

Section 11- Toxicological Information

Skin Corrosion/Irritation: no data

Serious Eye Damage/Irritation: no data

Respiratory/Skin Sensitization: no data

Germ Cell Mutagenicity: no data

Carcinogenicity: No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by IARC, NTP, or OSHA.

Reproductive Toxicity: no data

Specific Target Organ Toxicity – Single Exposure: no data

Specific Target Organ Toxicity – Repeated Exposure: no data

Aspiration Hazard: no data

Acute Toxicity: (calculated)

LD50 Oral, rat: > 37,000 mg/kg

LC50 Inhalation, rat (4 h): > 16.3 mg/l

LD50 Dermal, rabbit: > 11,700 mg/kg

Chronic Exposure: no data

Potential Health Effects – Miscellaneous: no data

Section 12 - Ecological Information

Toxicity:

LC50 (semi-static, 96 h): > 380 mg/l, *Danio rerio*

EC50 (static, 48 h): >270 mg/l, *Daphnia magna*

EC50 (static, 72 h): > 330 mg/l, *Desmodesmus subspicatus*

Persistence and Degradability: no data

Bioaccumulative Potential: no data

Mobility in Soil: no data

Other Adverse Effects: no data

Section 13 - Disposal Considerations

Disposal: Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore to not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

Section 14 - Transport Information

DOT
Not Regulated

IATA
Not Regulated

IMDG
Not Regulated

Section 15 - Regulatory Information

TSCA Inventory Status (40 CFR710): All components of this formulation are listed in the TSCA Inventory.

SARA 302 Components: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.


SARA 313 Components: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 313.

SARA 311/312 Hazards: none

California Proposition 65: This product contains a chemical known to the state of California to cause cancer.

16 - Other Information

| HMIS | |
|------|---|
| H | 1 |
| F | 1 |
| R | 0 |



NFPA

SDS Version: 1

Date Prepared: July 23, 2015

Glossary: ACGIH-American Conference of Governmental Industrial Hygienists; ANSI-American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS-Chemical Abstract Service; Chemtrec-Chemical Transportation Emergency Center (US); CHIP-Chemical Hazard Information and Packaging; DSL-Domestic Substances List; EC-Equivalent Concentration; EH40 (UK)-HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA-Emergency Planning and Community Right-To-Know Act; ESL-Effects screening levels; GHS-Globally Harmonized System of Classification and Labelling of Chemicals; HMIS-Hazardous Material Information Service; IATA-International Air Transport Association; IMDG-International Maritime Dangerous Goods Code; LC-Lethal Concentration; LD-Lethal Dose; LEL-Lower Explosion Level; NFPA-National Fire Protection Association; OEL-Occupational Exposure Limit; OSHA-Occupational Safety and Health Administration, US Dept. of Labor; PEL-Permissible Exposure Limit; SARA (Title III)-Superfund Amendments and Reauthorization Act; SARA 313-Superfund Amendments and Reauthorization Act, Section 313; SCBA-Self-Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TCEQ-Texas Commission on Environmental Quality; TLV-Threshold Limit Value; TSCA-Toxic Substances Control Act Public Law 94-469; TWA-Time Weighted Value; UEL-Upper Explosion Level; US DOT-US Department of Transportation; WHMIS-Workplace Hazardous Materials Information System.

Disclaimer: The information contained in this Safety Data Sheet (SDS) is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This SDS is prepared to comply with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) as prescribed by the United States (US) Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 (REACH).

Classifications of the chemical in accordance with 29 CFR 1910.1200, signal word, hazard and precautionary statement(s), symbol(s) and other information are based on listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS and EC No 1907/2006 and are considered trade secrets under US Federal Law (29 CFR and 40 CFR), Canadian Law (Health Canada Legislation), and European Union Directives.