



Fabric Specification Sheet

09/26/12

VTX 1070

107oz/yd² balanced glass quad

Fabric Width:	50.00	Inches		1270	MM		
Total Fabric Weight :	106.96	Oz/yd ²		3626.84	G/M ²	7	Gauge
Dry Fabric Thickness:		Inch			MM	3	Core (in)
Pounds Per Roll:	232	Pounds		106	Kilos	Shrink wrap	Packing
Lin Yards per Roll:	25	Yds.		75.00	Lin Ft		

STITCHING:

Stitch Type	Denier	Stitch Length	CPI
Polyester	100	4.23	6
Total Yarn percent of Total AW:	0.34%	Total Yarn AW	0.36 oz/yd²

ZERO:

Fiber Type	g/m ²	Oz/yd ²
E-glass	895.89	26.42
Total Zero percent of Total AW:	24.70%	Total Zero AW
		895.89 26.42

45 (-):

Fiber Type	g/m ²	Oz/yd ²
E-glass	911.42	26.88
Total -45 percent of Total AW:	25.13%	Total -45 AW
		911.42 26.88

NINETY:

Fiber Type	g/m ²	Oz/yd ²
E-glass	895.89	26.42
Total 90 percent of Total AW:	24.70%	Total 90' AW
		895.89 26.42

45 (+):

Fiber Type	g/m ²	Oz/yd ²
E-glass	911.42	26.88
Total +45 percent of Total AW:	25.13%	Total +45 AW
		911.42 26.88

MAT/VEIL:

Type	Oz/ft ²	g/m ²	Oz/yd ²
Total Mat/Veil percent of Total AW:			

V2 Composites, Inc. makes no warranties, expressed or implied, including merchantability or fitness for a particular purpose, except as expressly stated in writing.