



Fabric Specification Sheet

10/04/12

VX 160 EA

16oz/yd² +/-45 E-glass/aramid hybrid

Fabric Width:	50.00	Inches		1270	MM		
Total Fabric Weight :	15.95	Oz/yd ²		540.67	G/M ²	7	Gauge
Dry Fabric Thickness:		Inch			MM	3	Core (in)
Pounds Per Roll:	104	Pounds		47	Kilos	Box	Packing
Lin Yards per Roll:	75	Yds.		225.00	Lin Ft		

STITCHING:				
Stitch Type	Denier		Stitch Length	CPI
Polyester	100		3.63	7
Total Yarn percent of Total AW:	1.69%		Total Yarn AW	0.27 oz/yd²

ZERO:				
	Fiber Type		g/m ²	Oz/yd ²
Total Zero percent of Total AW:			Total Zero AW	

45 (-):				
	Fiber Type		g/m ²	Oz/yd ²
	E-glass		136.71	4.03
	Aramid		129.04	3.81
Total -45 percent of Total AW:	49.15%		Total -45 AW	265.76 7.84

NINETY:				
	Fiber Type		g/m ²	Oz/yd ²
Total 90 percent of Total AW:			Total 90' AW	

45 (+):				
	Fiber Type		g/m ²	Oz/yd ²
	E-glass		136.71	4.03
	Aramid		129.04	3.81
Total +45 percent of Total AW:	49.15%		Total +45 AW	265.76 7.84

MAT/VEIL:					
	Type		Oz/ft ²	g/m ²	Oz/yd ²
Total Mat/Veil percent of Total AW:					

V2 Composites, Inc. makes no warranties, expressed or implied, including merchantability or fitness for a particular purpose, except as expressly stated in writing.